

DATA
OUTPUT

MOISTURE ANALYZER



calibration weight (included)

- LCD screen
- High sensitivity temperature and humidity sensor
- Ring halogen lamp heating evenly, shorten drying time



8701-RM40

SPECIFICATION

Code	8701-RM20	8701-RM30	8701-RM40
Maximum weighing	120g	120g	120g
Resolution (d)	5mg	1mg	0.1mg
Accuracy	sample < 10g ±10%	±0.5%	±0.2%
for moisture	sample ≥ 10g ±5%	±0.3%	±0.1%
Operation temperature	13~25°C		
Verification interval	2.5s		
Warm-up time	20~30 mins		
Weighing pan size	Ø90 mm		
Heating source	halogen lamp(450W)		
Range for heating temperature	60~200°C		
Heating time setting	0~99 mins		
Heating mode	standard heating, step heating, rapid heating		
Shutdown mode	automatic shutdown, manual shutdown, timed shutdown		
Output	RS232C		
Power supply	220V, 50/60Hz		
Dimension (L×W×H)	330×210×340mm		

STANDARD DELIEVERY

Main unit	1pc
Weight	1pc

OPTIONAL ACCESSORY

RS232 cable	8304-CABLE*
Printer	8303-PRINTER

* Used to connect computers