


5116

HSS DIN 335 C



3z

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
●	○			○		●	●		●	●	●	●		○			
20-30	12-18			4-10		15-24	9-13		15-80	25-60	60-90	12-70		4-10			

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative



Ø mm	d mm
4,30	4
5,00	4
5,30	4
5,80	5
6,00	5
6,30	5
7,00	6
7,30	6
8,00	6
8,30	6
9,40	6
10,00	6
10,40	6
11,50	8

L mm	
40	1
40	1
40	1
45	1
45	1
45	1
50	1
50	1
50	1
50	1
50	1
50	1
56	1

Ø mm	d mm
12,40	8
13,40	8
15,00	10
16,50	10
19,00	10
20,50	10
23,00	10
25,00	10
26,00	10
28,00	12
30,00	12
31,00	12
40,00	13

L mm	
56	1
56	1
60	1
60	1
63	1
63	1
67	1
67	1
67	1
71	1
71	1
71	1
80	1