


4106

HSSCO DIN 208

Form.
B



Tol.
H7

ISO
521

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
● 8-14	● 6-8	○ 4-6		● 6-8	○ 4-6	● 12-16	● 6-12		● 14-25	● 12-25	○ 12-16	● 8-14	○ 1-3	● 2-8			

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative



▶	△	Ø mm				▶	△	Ø mm				▶	△	Ø mm			
			L mm	l mm	📦				L mm	l mm	📦				L mm	l mm	📦
	1	4,00	129	19	1		2	16,00	210	52	1						
	1	5,00	133	23	1		2	16,50	214	54	1						
	1	5,50	138	26	1		2	17,00	214	54	1						
	1	6,00	138	26	1		2	18,00	219	56	1						
	1	6,50	144	28	1		2	19,00	223	58	1						
	1	7,00	150	31	1		2	20,00	228	60	1						
	1	7,50	150	31	1		2	21,00	232	62	1						
	1	8,00	156	33	1		2	22,00	237	64	1						
	1	8,50	156	33	1		2	23,00	241	66	1						
	1	9,00	162	36	1		3	24,00	268	68	1						
	1	9,50	162	36	1		3	25,00	268	68	1						
	1	10,00	168	38	1		3	26,00	273	70	1						
	1	10,50	168	38	1		3	27,00	277	71	1						
	1	11,00	175	41	1		3	28,00	277	71	1						
	1	11,50	175	41	1		3	29,00	281	73	1						
	1	12,00	182	44	1		3	30,00	281	73	1						
	1	12,50	182	44	1		3	31,00	285	75	1						
	1	13,00	182	44	1		4	32,00	317	77	1						
	1	13,50	189	47	1		4	34,00	321	78	1						
	1	14,00	189	47	1		4	35,00	321	78	1						
	2	14,50	204	50	1		4	36,00	325	79	1						
	2	15,00	204	50	1		4	38,00	329	81	1						
	2	15,50	210	52	1		4	40,00	329	81	1						