



Integrated Type Keyless Drill Chucks



FOR DRILL ONLY , NOT FOR END MILL OR TAP



FOR SPECIFICATION PLEASE SEE P.C76

The main-shafts is of integrated type, which is much more superior than the traditional design. The major features are as follows:

- Extremely rigid construction. Accuracy is same as page C66
- The accumulative tolerances can be reduced to a minimum, since the traditional mechanism requiring an ARBOR to connect the Drill Chucks which will generate the accumulative tolerances. The Integrated type Keyless Drill Chuck is designed to solve this problem totally.
- Prevent the Drill Chucks from falling out.
- Extremely safe in operation.
- 2500 R.P.M.

ACCURACY

| ITEM NO. | d mm | L mm | Max Tolerance mm | Torque kgf-cm |
|----------|------|------|------------------|---------------|
| INT-8 | 3 | 25 | 0.05 | 160 |
| | 6 | 30 | | |
| | 8 | | | |
| INT-10 | 3 | 25 | 0.05 | 260 |
| | 6 | 30 | | |
| | 10 | | | |
| INT-13 | 5 | 30 | 0.05 | 400 |
| | 10 | 25 | | |
| | 13 | | | |
| INT-16 | 5 | 25 | 0.05 | 480 |
| | 10 | 30 | | |
| | 16 | | | |



STANDARD ACCES.

