

# SHOCKPROOF DIAL INDICATORS

SHOCK  
PROOF

JEWELLED  
BEARING

**INSPECTION  
CERTIFICATE**  
TRACEABLE TO NIST

- Meet DIN878
- Shockproof
- Jeweled bearing
- Supplied with limit pointers and bezel clamp
- Optional accessory: backs (page 176~177), contact points (page 173~175)



2314-10A

Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	Remark
2314-3FA *	3mm	0.01mm	12 $\mu$ m	3 $\mu$ m	1mm	0-100	flat back
2314-5FA *	5mm	0.01mm	14 $\mu$ m	3 $\mu$ m	1mm	0-100	flat back
2314-10FA *	10mm	0.01mm	17 $\mu$ m	3 $\mu$ m	1mm	0-100	flat back
2314-3A *	3mm	0.01mm	12 $\mu$ m	3 $\mu$ m	1mm	0-100	lug back
2314-5A *	5mm	0.01mm	14 $\mu$ m	3 $\mu$ m	1mm	0-100	lug back
2314-10A *	10mm	0.01mm	17 $\mu$ m	3 $\mu$ m	1mm	0-100	lug back

\* Supplied with manufacturer inspection certificate traceable to NIST USA

