



- Meet DIN863-4
- 2-12mm: graduation 0.001mm
12-300mm: graduation 0.005mm
- Ratchet stop
- Optional accessory: setting rings (code **6312**),
micrometer stand and clamp (code **6301** and **6301-2**)

Individual

										(mm)
Code	Range	Type	Accuracy	Setting ring	Extension rod (included)	L	a	b	c	
3227-2 *	2-2.5mm	A (two points)	6µm	Ø2.5 (included)	—	12	—	—	—	
3227-3 *	2.5-3mm	A (two points)	6µm	Ø2.5 (included)	—	12	—	—	—	
3227-4 *	3-4mm	A (two points)	6µm	Ø4 (included)	—	22	—	—	—	
3227-5 *	4-5mm	A (two points)	6µm	Ø5 (included)	—	22	—	—	—	
3227-6 *	5-6mm	A (two points)	6µm	Ø6 (included)	—	22	—	—	—	
3227-8 *	6-8mm	B (three points)	4µm	Ø6 (included)	100	54.5	1.5	2.5	—	
3227-10 *	8-10mm	B (three points)	4µm	Ø8 (included)	100	54.5	1.5	2.5	—	
3227-12 *	10-12mm	B (three points)	4µm	Ø10 (included)	100	54.5	1.5	2.5	—	
3227-16 *	12-16mm	C (three points)	4µm	Ø16 (included)	150	80	0.5	6	4.5	
3227-20 *	16-20mm	C (three points)	4µm	Ø16 (included)	150	80	0.5	6	4.5	
3227-25 *	20-25mm	C (three points)	4µm	Ø25 (included)	150	90	0.5	8	6	
3227-30 *	25-30mm	C (three points)	4µm	Ø25 (included)	150	90	0.5	8	6	
3227-40 *	30-40mm	C (three points)	4µm	Ø40 (included)	150	97	0.5	14	12	
3227-50 *	40-50mm	C (three points)	5µm	Ø40 (included)	150	97	0.5	14	12	
3227-63 *	50-63mm	D (three points)	5µm	Ø62 (included)	150	114	0.5	17.5	14.5	
3227-75 *	62-75mm	D (three points)	5µm	Ø62 (included)	150	114	0.5	17.5	14.5	
3227-88 *	75-88mm	D (three points)	5µm	Ø87 (included)	150	114	0.5	17.5	14.5	
3227-100 *	87-100mm	D (three points)	5µm	Ø87 (included)	150	114	0.5	17.5	14.5	
3227-125 *	100-125mm	D (three points)	6µm	optional	150	140	0.9	29	25	
3227-150 *	125-150mm	D (three points)	6µm	optional	150	140	0.9	29	25	
3227-175 *	150-175mm	D (three points)	7µm	optional	150	140	0.9	29	25	
3227-200 *	175-200mm	D (three points)	7µm	optional	150	140	0.9	29	25	
3227-225	200-225mm	D (three points)	8µm	optional	150	140	0.9	29	25	
3227-250	225-250mm	D (three points)	8µm	optional	150	140	0.9	29	25	
3227-275	250-275mm	D (three points)	9µm	optional	150	140	0.9	29	25	
3227-300	275-300mm	D (three points)	9µm	optional	150	140	0.9	29	25	

micrometer stand
with clamp (optional)



setting ring



2-100mm: included
100-300mm: **optional**

extension rod



included



3227-504

Set

Code	Range	Micrometers included	Setting ring (included)	Extension rod (included)
3227-232 *	2-3mm	2-2.5mm, 2.5-3mm	Ø2.5mm	—
3227-363 *	3-6mm	3-4mm, 4-5mm, 5-6mm	Ø4mm, Ø5mm, Ø6mm	—
3227-123 *	6-12mm	6-8mm, 8-10mm, 10-12mm	Ø6mm, Ø8mm, Ø10mm	100mm
3227-202 *	12-20mm	12-16mm, 16-20mm	Ø16mm	150mm
3227-504 *	20-50mm	20-25mm, 25-30mm, 30-40mm, 40-50m	Ø25mm, Ø40mm	150mm
3227-1004 *	50-100mm	50-63mm, 62-75mm, 75-88mm, 87-100mm	Ø62mm, Ø87mm	150mm

* Supplied with manufacturer inspection certificate