



PEN-TYPE CONDUCTIVITY TESTER (BASIC TYPE) CODE 0416-EB01

- Suitable for water quality testing, aquaculture, food processing, scientific research, etc.
- Mini design with an electrode diameter of 10mm
- Manual temperature compensation
- With reading stabilization reminder function
- Replaceable electrodes
- Low voltage alarm
- CR2032 battery, automatic power off
- Probe protection level: IP54



SPECIFICATION

Measuring range	(0~99.9) μ S/cm, (100~999) μ S/cm, (1.00~9.99) mS/cm, (10.00~99.99)mS/cm, (100~199.9)mS/cm
Resolution	0.01 μ S/cm, 0.1 μ S/cm, 1 μ S/cm, 0.01mS/cm
Accuracy	$\pm 1.5\%$ FS
Temperature compensation range	0~99.9°C (manual)
Calibration mode	1 point (automatic recognition), electrode constant calibration
Standard solution	1413 μ S/cm
Power supply	CR2032 battery
Dimension (L×W×H)	50×188×17mm
Weight	60g

STANDARD DELIVERY

Main unit	1 pc
Conductivity electrode (0416-EB01-E)	1 pc
Calibration powder (0416-EB01-S)*	2 pcs

* Dissolve in distilled water to 50mL