


# DIGITAL OFFSET CENTERLINE CALIPERS

DATA  
OUTPUT

preset buttons



1192-150A




- Measure hole center distance in the same or offset planes
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Made of stainless steel

## With data interface

| Code       | Range             | Accuracy | c  | ØD | L1 | L2  | L    | Data output cable (optional) |
|------------|-------------------|----------|----|----|----|-----|------|------------------------------|
| 1192-150A  | 10-150mm/0.4-6"   | ±0.05mm  | 16 | 10 | 46 | 79  | 236  | 7315-21, 7302-21             |
| 1192-200A  | 10-200mm/0.4-8"   | ±0.07mm  | 16 | 10 | 46 | 79  | 286  | 7315-21, 7302-21             |
| 1192-300A  | 10-300mm/0.4-12"  | ±0.09mm  | 16 | 10 | 46 | 79  | 396  | 7315-21, 7302-21             |
| 1192-500A  | 20-500mm/0.8-20"  | ±0.09mm  | 24 | 20 | 52 | 112 | 725  | 7315-22, 7302-22             |
| 1192-1000A | 30-1000mm/1.2-40" | ±0.12mm  | 31 | 30 | 52 | 112 | 1255 | 7315-22, 7302-22             |
| 1192-1500A | 30-1500mm/1.2-60" | ±0.15mm  | 31 | 30 | 75 | 120 | 1760 | 7315-22, 7302-22             |

(mm)



## Built-in wireless (receiver code 7315-2/3/6/7/8 is required)

(mm)

| Code        | Range            | Accuracy | c  | ØD | L1 | L2  | L   |
|-------------|------------------|----------|----|----|----|-----|-----|
| 1192-150AWL | 10-150mm/0.4-6"  | ±0.05mm  | 16 | 10 | 46 | 79  | 236 |
| 1192-200AWL | 10-200mm/0.4-8"  | ±0.07mm  | 16 | 10 | 46 | 79  | 286 |
| 1192-300AWL | 10-300mm/0.4-12" | ±0.09mm  | 16 | 10 | 46 | 79  | 396 |
| 1192-500AWL | 20-500mm/0.8-20" | ±0.09mm  | 24 | 20 | 52 | 112 | 725 |