## **DIAL CALIPERS**



SHOCK PROOF

- Shockproof dial indicator
- Made of stainless steel

Dial indicator graduation: 0.02mm

(mm)

| Code       | Range   | Accuracy | Thumb roller | L   | a  | b    | C  | d  | D     | t   |
|------------|---------|----------|--------------|-----|----|------|----|----|-------|-----|
| 1312-150A* | 0-150mm | ±0.03mm  | with         | 235 | 21 | 16.5 | 16 | 40 | Ø39   | 6.5 |
| 1312-200A* | 0-200mm | ±0.03mm  | with         | 288 | 24 | 19   | 16 | 48 | Ø39   | 6.5 |
| 1312-300A* | 0-300mm | ±0.03mm  | with         | 410 | 28 | 22   | 20 | 62 | Ø44.5 | 7.5 |

Dial indicator graduation: 0.01mm (mm)

| Code       | Range   | Accuracy | Thumb roller | L   | a  | b    | C  | d  | D     | t   |
|------------|---------|----------|--------------|-----|----|------|----|----|-------|-----|
| 1311-150A* | 0-150mm | ±0.03mm  | with         | 235 | 21 | 16.5 | 16 | 40 | Ø39   | 6.5 |
| 1311-200A* | 0-200mm | ±0.03mm  | with         | 288 | 24 | 19   | 16 | 48 | Ø39   | 6.5 |
| 1311-300A* | 0-300mm | ±0.03mm  | with         | 410 | 28 | 22   | 20 | 62 | Ø44.5 | 7.5 |

<sup>\*</sup>Supplied with manufacturer inspection certificate



1312-150A

