

Montagelineale Aluminium ULTRA *active*



- ▶ DIN 874
- ▶ I-förmiger Querschnitt
- ▶ geringes Gewicht
- ▶ ab 1500mm mit Erleichterungsbohrungen
- ▶ Lieferung im Holzkasten
- ▶ Beschichtungseigenschaften:
 - Härte HV 80
 - Zugfestigkeit 47kg/mm²
 - Streckgrenze 110kg/mm²

Assembling straightedges aluminium ULTRA *active*

- ▶ DIN 874
- ▶ I-profile
- ▶ Light weight
- ▶ from 1500mm with relief bores
- ▶ Delivered in wooden box
- ▶ Coating characteristics:
 - Hardness HV 80
 - Tensile strength 47kg/mm²
 - Yield point 110kg/mm²

Alle Preise abzüglich Rabatt! / Rabatt anfragen
All prices less discount! / Ask for discount

+49 (0) 6021 42999 00

l mm	t mm	W kg	GG DIN 874 Güte / Grade	Nº
500	60 x 30	0,8	0	1682300
750	60 x 30	1,2	0	1682300x
1000	100 x 40	3,0	0	1682301
1500	100 x 40	4,5	1	1682302
2000	100 x 40	6,0	1	1682303
2500	150 x 80	17,5	1	1682304
3000	150 x 80	21,0	2	1682305

NEW



No. 1682301



No. 1682304