

# Bügelmessschrauben für Zahnweitenmessung



- ▶ Genauigkeit besser als DIN 863
- ▶ Spindelsteigung 1,0mm
- ▶ Ableseteile mattverchromt
- ▶ Stahlmessflächen gehärtet
- ▶ Spindelklemmung mit Ring
- ▶ Friktionskupplung
- ▶ Leichtmetallbügel
- ▶ Handwärmeschutz
- ▶ Lieferung ohne Etui und ohne Einstellmaß

**2052 3.. :**  
Messflächen Ø 35mm, Modul 2 – 10

**2052 4.. :**  
Messflächen Ø 50mm, Modul 2 – 30

**2037 1.. :**  
Einstellmaße

**2027 6.. :**  
Holzetuis

|  mm |  mm |  kg | Nº       | Nº       | Nº       | Nº       |
|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|----------|----------|----------|----------|
| 300 – 350                                                                              | 0,01                                                                                   | 1,65                                                                                   | 2052 301 | 2052 401 | 2037 112 | 2027 601 |
| 350 – 400                                                                              | 0,01                                                                                   | 1,95                                                                                   | 2052 302 | 2052 402 | 2037 114 | 2027 602 |
| 400 – 450                                                                              | 0,01                                                                                   | 2,3                                                                                    | 2052 303 | 2052 403 | 2037 116 | 2027 603 |
| 450 – 500                                                                              | 0,01                                                                                   | 2,45                                                                                   | 2052 304 | 2052 404 | 2037 118 | 2027 604 |
| 500 – 550                                                                              | 0,01                                                                                   | 2,55                                                                                   | 2052 305 | 2052 405 | 2037 120 | 2027 605 |
| 550 – 600                                                                              | 0,01                                                                                   | 3,15                                                                                   | 2052 306 | 2052 406 | 2037 122 | 2027 606 |
| 600 – 650                                                                              | 0,01                                                                                   | 3,45                                                                                   | 2052 307 | 2052 407 | 2037 124 | 2027 607 |
| 650 – 700                                                                              | 0,01                                                                                   | 3,85                                                                                   | 2052 308 | 2052 408 | 2037 126 | 2027 608 |
| 700 – 750                                                                              | 0,01                                                                                   | 4,05                                                                                   | 2052 309 | 2052 409 | 2037 128 | 2027 609 |
| 750 – 800                                                                              | 0,01                                                                                   | 4,25                                                                                   | 2052 310 | 2052 410 | 2037 130 | 2027 610 |
| 800 – 850                                                                              | 0,01                                                                                   | 4,45                                                                                   | 2052 311 | 2052 411 | 2037 132 | 2027 611 |
| 850 – 900                                                                              | 0,01                                                                                   | 5,05                                                                                   | 2052 312 | 2052 412 | 2037 134 | 2027 612 |
| 900 – 950                                                                              | 0,01                                                                                   | 5,95                                                                                   | 2052 313 | 2052 413 | 2037 136 | 2027 613 |
| 950 – 1000                                                                             | 0,01                                                                                   | 6,25                                                                                   | 2052 314 | 2052 414 | 2037 138 | 2027 614 |

# External micrometers for gear tooth measurements

- ▶ Accuracy better than DIN 863
- ▶ Sindle pitch 1.0mm
- ▶ Satin chrome reading parts
- ▶ Hardened steel measuring faces
- ▶ Spindle clamping with ring
- ▶ Friction clutch
- ▶ Light metal frame
- ▶ Insulated pads
- ▶ Delivered without case and without setting gauge

**2052 3.. :**  
Measuring faces Ø 35mm, module 2 – 10

**2052 4.. :**  
Measuring faces Ø 50mm, module 2 – 30

**2037 1.. :**  
Setting gauges

**2027 6.. :**  
Wooden boxes

