

► Vertical toggle clamp

Design and use 299100:

- horizontal toggle clamp, with open holding arm and horizontal base
- galvanised and passivated
- ergonomic handle made of red, oil-resistant plastic-
- from size 2 case-hardened and pre-lubricated bearing bushes
- with tempered and galvanised clamping screw, slidable and captive
- safety spanner with finger protection
- for mounting on plates etc.

Note:

Also available in stainless steel

Design 299101:

- vertical clamp with twist-proof bushes (except size 1)
- rivets made of stainless steel
- galvanised and passivated
- media resistant plastic handle
- safety spanner
- long support arm guidance
- large operating space for the hand in open position

Delivery:




Incl. pressure spindle



299100



299101



Größe			0	1	2	3	4	5	6
299100 			●	●	●	●	●	●	○
299101 			—	●	●	●	●	○	—
Hole distance C × M	mm	299100	11 × 23	18 × 24	25 × 27	20 × 32,5	32 × 43,5	45 × 50	50,5 × 67,5
		299101	—	16 × 23,4	12,7 × 26,9	19 × 32	32 × 45	32 × 45	—
Bore- D	mm	299100	4,5	4,5	5,5	7,5	8,6	8,5	13
		299101	—	4,4	5,1	7,1	8,3	8,7	—
Clamping height H	mm	299100	18	19	23	33	42,5	55,8	81
		299101	—	19	23	32	42	50,8	—
Tensioning force F1	N	299100	500	600	800	1.200	1.700	3.000	3.400
		299101	—	—	—	—	—	—	—
Tensioning force F2	N	299100	700	1.100	1.200	2.500	3.000	5.000	5.500
		299101	—	450	1.500	2.500	3.400	3.600	—
Total height H1	mm	299100	81	98,5	139,5	186	221	224	333
		299101	—	77	111	175	218	224	—
Total length L1	mm	299100	49	61	78	112	141	195	231
		299101	—	50,4	69,9	90	143	176	—
Clamping screw		299100	M4 × 25	M5 × 30	M6 × 35	M8 × 45	M8 × 65	M12 × 80	M12 × 110
		299101	—	M5 × 30	M6 × 50	M8 × 45	M10 × 75	M12 × 80	—