

WATERPROOF DIGITAL OUTSIDE MICROMETERS (WITHOUT DATA OUTPUT)

- Resolution 0.001mm/0.00005"
- IP65 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC
- No data output
- Automatic power off
- Carbide measuring faces
- Supplied with spherical anvil
- Setting standards are included (except 0-25mm/0-1")

IP65
WATERPROOF

**ATTENTION: NO
DATA OUTPUT**

**INSPECTION
CERTIFICATE**
TRACEABLE TO DKD




Ratchet stop type

(mm)

Code	Range	Accuracy	L	a	b	c
3108-25A *	0-25mm/0-1"	±2µm	34.5	6	25	3
3108-50A *	25-50mm/1-2"	±2µm	59.5	8	32	3
3108-75A *	50-75mm/2-3"	±3µm	84.5	8	44.5	3
3108-100A *	75-100mm/3-4"	±3µm	109.5	8	57	3
3108-125A	100-125mm/4-5"	±3µm	135	10	70	3
3108-150A	125-150mm/5-6"	±3µm	160.5	10	82	3
3108-175A	150-175mm/6-7"	±4µm	186	12	94.5	5.5
3108-200A	175-200mm/7-8"	±4µm	211.5	12	107	5.5



3108-25A



Friction thimble type

(mm)

Code	Range	Accuracy	L	a	b	c
3108-25FA *	0-25mm/0-1"	±2µm	34.5	6	25	3

Set

Code	Range	Micrometers included	Packaging
3108-753A *	0-75mm/0-3"	3108-25A, 3108-50A, 3108-75A	blow mould case
3108-1004A *	0-100mm/0-4"	3108-25A, 3108-50A, 3108-75A, 3108-100A	blow mould case
3108-1506A	0-150mm/0-6"	3108-25A, 3108-50A, 3108-75A, 3108-100A, 3108-125A, 3108-150A	aluminum box



3108-753A



3108-1506A

* Supplied with manufacturer inspection certificate traceable to DKD Germany