


**NON-ROTATING
SPINDLE**

NON-ROTATING SPINDLE UNIVERSAL MICROMETERS



3280-25A

- Meet DIN863-3
- Graduation 0.01mm
- Non-rotating spindle
- Ratchet stop
- Supplied with 7 pairs of anvil/spindle tip
- Setting standards are included (except 0-25mm)
- Optional accessory: 55° anvil/spindle tip (code **3280-SP1** and **3280-SP2**)



Unit: mm

Anvil/spindle tip (included)

Unit: mm

| | | |
|------------|--|--|
| Flat | | |
| Spherical | | |
| Spline | | |
| Disk | | |
| Blade | | |
| Knife-edge | | |
| Point | | |

55° anvil/spindle tip (optional)

Unit: mm

| | | |
|------------------------------------|--|--|
| Code 3280-SP1 Knife-edge | | |
| Code 3280-SP2 Point | | |

| Code | Range | Accuracy | L | b |
|------------------|-----------|----------|-------|-------|
| 3280-25A | 0-25mm | 4µm | 42mm | 26mm |
| 3280-50A | 25-50mm | 4µm | 67mm | 38mm |
| 3280-75A | 50-75mm | 5µm | 92mm | 50mm |
| 3280-100A | 75-100mm | 5µm | 118mm | 62mm |
| 3280-125A | 100-125mm | 6µm | 143mm | 70mm |
| 3280-150A | 125-150mm | 6µm | 168mm | 82mm |
| 3280-175A | 150-175mm | 7µm | 192mm | 95mm |
| 3280-200A | 175-200mm | 7µm | 217mm | 107mm |