

DIGITAL V-ANVIL MICROMETERS


IP65
WATERPROOF

DATA
OUTPUT



3590-153A

- Measure the diameter of parts or cutting tools with odd grooves, such as taps, reamers and end mills
- Resolution 0.001mm/0.00005"
- IP65 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC
- Data output
- Automatic power off
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards
- Optional accessory: data output cable (code **7315-30**, **7302-30**)



Code	Range	Flutes	Accuracy	α	Type
3590-153A	1-15mm/0.04-0.6"	3	$\pm 4\mu\text{m}$	60°	A
3590-203A	5-20mm/0.2-0.8"	3	$\pm 4\mu\text{m}$	60°	B
3590-353A	20-35mm/0.8-1.4"	3	$\pm 5\mu\text{m}$	60°	B
3590-503A	35-50mm/1.4-2.0"	3	$\pm 5\mu\text{m}$	60°	B
3590-653A	50-65mm/2.0-2.6"	3	$\pm 6\mu\text{m}$	60°	B
3590-803A	65-80mm/2.6-3.2"	3	$\pm 6\mu\text{m}$	60°	B
3590-953A	80-95mm/3.2-3.6"	3	$\pm 6\mu\text{m}$	60°	B
3590-255A	5-25mm/0.2-1.0"	5	$\pm 4\mu\text{m}$	108°	B

Code	Range	Flutes	Accuracy	α	Type
3590-455A	25-45mm/1.0-1.8"	5	$\pm 5\mu\text{m}$	108°	B
3590-655A	45-65mm/1.8-2.6"	5	$\pm 6\mu\text{m}$	108°	B
3590-855A	65-85mm/2.6-3.4"	5	$\pm 6\mu\text{m}$	108°	B
3590-1055A	85-105mm/3.4-4.2"	5	$\pm 6\mu\text{m}$	108°	B
3590-257A	5-25mm/0.2-1.0"	7	$\pm 4\mu\text{m}$	$128^\circ 34' 17''$	B
3590-457A	25-45mm/1.0-1.8"	7	$\pm 4\mu\text{m}$	$128^\circ 34' 17''$	B
3590-657A	45-65mm/1.8-2.6"	7	$\pm 5\mu\text{m}$	$128^\circ 34' 17''$	B
3590-857A	65-85mm/2.6-3.4"	7	$\pm 5\mu\text{m}$	$128^\circ 34' 17''$	B