


5118

HSS DIN 335 C



3z

TIALN

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
● 25-35	○ 15-20			○ 6-12		● 20-30	● 12-16		● 20-100	● 30-75	● 75-115	● 15-90		○ 8-12			

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative



Ø mm	d mm
4,30	4
5,00	4
5,30	4
5,80	5
6,00	5
6,30	5
7,00	6
7,30	6
8,00	6
8,30	6
9,40	6
10,00	6
10,40	6
11,50	8



L mm	
40	1
40	1
40	1
45	1
45	1
45	1
50	1
50	1
50	1
50	1
50	1
50	1
56	1



Ø mm	d mm
12,40	8
13,40	8
15,00	10
16,50	10
19,00	10
20,50	10
23,00	10
25,00	10
26,00	12
28,00	12
30,00	12
31,00	12
40,00	13



L mm	
56	1
56	1
60	1
60	1
63	1
63	1
67	1
67	1
71	1
71	1
71	1
71	1
80	1