HSS END MILLS

FLAT SHANK **E2535** SERIES

FLAT SHANK **EQ535** SERIES

HSSCo8, 2 FLUTE SHORT LENGTH BALL NOSE

HSSCo8, 2 SCHNEIDEN KURZ STIRNRADIUS

Fraise HSSCo8, 2 dents, hémisphérique, courte

2 TAGLIENTI, SEMISFERICA, SERIE CORTA - HSSCo8

HSS Co8 | DIN 327 | 2 | ≈30° | R ±0.02 | DIN 1835B | UNCOATED | TiAlN

p.C673-674

Recommendec ToolHolder	FlatShank	Page	PlainShank	Page
◎	ENDMILLHOLDER	D118-137	POWERMILLINGCHUCK	D161-176
◎	-	-	ERCOLLETCHUCK	D73-116
			SKSUMCHUCK	D183-201

Unit : mm

EDP No. UNCOATED	EDP No. TiAlN	Radius of Ball Nose R (±0.02)	Mill Diameter	Shank Diameter h6	Length of Cut	Overall Length
E2535020	**EQ535020**	R1.0	**2.0**	6	4	48
E2535025	**EQ535025**	R1.25	**2.5**	6	5	49
E2535030	**EQ535030**	R1.5	**3.0**	6	5	49
E2535035	**EQ535035**	R1.75	**3.5**	6	6	50
E2535040	**EQ535040**	R2.0	**4.0**	6	7	51
E2535045	**EQ535045**	R2.25	**4.5**	6	7	51
E2535050	**EQ535050**	R2.5	**5.0**	6	8	52
E2535055	**EQ535055**	R2.75	**5.5**	6	8	52
E2535060	**EQ535060**	R3.0	**6.0**	6	8	52
E2535070	**EQ535070**	R3.5	**7.0**	10	10	60
E2535080	**EQ535080**	R4.0	**8.0**	10	11	61
E2535090	**EQ535090**	R4.5	**9.0**	10	11	61
E2535100	**EQ535100**	R5.0	**10.0**	10	13	63
E2535110	**EQ535110**	R5.5	**11.0**	12	13	70
E2535120	**EQ535120**	R6.0	**12.0**	12	16	73
E2535130	**EQ535130**	R6.5	**13.0**	12	16	73
E2535140	**EQ535140**	R7.0	**14.0**	12	16	73
E2535150	**EQ535150**	R7.5	**15.0**	12	16	73
E2535160	**EQ535160**	R8.0	**16.0**	16	19	79
E2535170	**EQ535170**	R8.5	**17.0**	16	19	79
E2535180	**EQ535180**	R9.0	**18.0**	16	19	79
E2535190	**EQ535190**	R9.5	**19.0**	16	19	79
E2535923	**EQ535923**	R10.0	**20.0**	16	22	82
E2535200	**EQ535200**	R10.0	**20.0**	20	22	88
E2535220	**EQ535220**	R11.0	**22.0**	20	22	88
E2535922	**EQ535922**	R11.0	**22.0**	25	22	98
E2535240	**EQ535240**	R12.0	**24.0**	25	26	102
E2535250	**EQ535250**	R12.5	**25.0**	25	26	102
E2535260	**EQ535260**	R13.0	**26.0**	25	26	102
E2535280	**EQ535280**	R14.0	**28.0**	25	26	102
E2535300	**EQ535300**	R15.0	**30.0**	25	26	102
E2535320	**EQ535320**	R16.0	**32.0**	32	32	112

Mill Dia. Tolerance (mm)	Shank Dia. Tolerance
0 ~ - 0.03	h6

▶Other shank design on your reguest.

▶TiN and TiCN Coatings are available on your request.

◎ : Excellent ○ : Good

ISO	P											M			K					
Material Description	Non-alloy steel					Low alloy steel				High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc		13	25	28	32	10	29	32	38	15	35	15	23	10	10	26	3	25		21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommend	◎	◎	◎	◎	○	◎	◎	○	○	◎	○									

ISO	N										S							H			
Material Description	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel		Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc											15	30	25	38	34			55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400 Rm	1050 Rm	550	630	400	550
Recommend	○	○	○	○	○																