

▶ Keyless drill chuck **Supra**



Design:

- self-clamping, robust retaining ring, short version, low weight
- automatic retightening during drilling proportional to clamping force to maintain the gripping force even under difficult conditions

Use:

For rapid clamping and releasing of tools on stationary or hand-guided power drills

N = heavy industrial version,

for stationary drills

S = light weight version,

mainly for hand-held impact drills

*shortened: B16 by 2.5 mm, B18 by 7 mm.



| Item no. | 214500 Taper reception | Clamping width from-to mm | A4 mm | B3 mm | B4 mm | C2 |
|----------|---------------------------|---------------------------------|----------|----------|----------|------|
| 6N | ● | 0-6,5 | 32 | 59,5 | 65,6 | B10 |
| 6N-1 | ● | 0-6,5 | 32 | 59,5 | 65,6 | B12 |
| 8N | ● | 0-8 | 35,8 | 67 | 73,4 | B12 |
| 10N | ● | 0-10 | 40,2 | 79,5 | 86,1 | B12 |
| 10N-1 | ● | 0-10 | 40,2 | 82,5 | 89,1 | B16* |
| 13S | ● | 1-13 | 40,2 | 78,8 | 86,1 | B12 |
| 13S-1 | ● | 1-13 | 40,2 | 82,3 | 89,6 | B16* |
| 13N | ● | 1-13 | 46 | 93 | 101,5 | B16* |
| 16S | ● | 3-16 | 46 | 88,5 | 98,5 | B16* |
| 16S-1 | ● | 3-16 | 46 | 92 | 102 | B18* |
| 16N | ● | 3-16 | 51 | 96,5 | 106,8 | B16* |
| 16N-1 | ● | 3-16 | 51 | 96,5 | 106,8 | B18* |