





magnet pick up(included)

SPECIFICATION

| OI LOI | SPECIFICATION | | | | |
|--------------|-----------------|----------------------------------|--|--|--|
| Lens | diameter | 5.2mm | | | |
| | pixel | 0.4M | | | |
| | depth of field | 30~80mm | | | |
| | angle of view | 72° | | | |
| | Illumination | 8 levels | | | |
| | dust/waterproof | IP67 | | | |
| Cable | length | 1m | | | |
| | type | memory (can be set at any shape) | | | |
| Main unit | display | 4.3" LCD | | | |
| | function | take picture, take video | | | |
| | file format | picture: JPG, video: AVI | | | |
| | image zoom | 2X | | | |
| | memory card | memory card(optional) | | | |
| | output | micro USB | | | |
| | power supply | AA battery | | | |
| | dimension | 154×32.5×87.5mm | | | |
| Weight | | 280g | | | |

STANDARD DELIVERY

| Main unit | 1pc |
|----------------|------|
| Hook | 1pc |
| Magnet pick up | 1pc |
| AA battery | 4pcs |

OPTIONAL ACCESSORY

| 32G memory card | ISV-E40-CARD |
|-----------------|----------------|
| Card reader | ISV-E40-READER |

OPERATING ENVIRONMENT

| Operating temperature | -10~50°C |
|-----------------------|----------|
| Storage temperature | -20~60°C |
| Operating humidity | 15%~85% |