



PCE Americas Inc.
711 Commerce Way
Suite 8
Jupiter
FL-33458
USA
From outside US: +1
Tel: (561) 320-9162
Fax: (561) 320-9176
info@pce-americas.com

PCE Instruments UK Ltd.
Units 12/13
Southpoint Business Park
Ensign way
Hampshire / Southampton
United Kingdom, SO31 4RF
From outside UK: +44
Tel: (0) 2380 98703 0
Fax: (0) 2380 98703 9
info@pce-instruments.com

www.pce-instruments.com/english
www.pce-instruments.com

Technical Refractometer PCE-DRS 1

PCE-DRS 1 Handheld Digital Refractometer

**IP65-rated salinity or salt content (% , ‰) / specific gravity (SG) / refractive index (nD)
refractometer with easy-to-read LCD**

PCE-DRS 1 is a handheld digital refractometer used to determine the salinity or salt content (% , ‰), specific gravity (SG) and refractive index (nD) of liquid. This IP65-rated digital refractometer features automatic temperature compensation (ATC) from +10 ... +40 °C / +50 ... +104 °F, as well as a large, easy-to-read LCD that shows both the measured value and the temperature.

- Automatic temperature compensation (ATC) from +10 ... +40 °C / +50 ... +104 °F
- Handheld and portable
- User-friendly 3-button operation
- Fast and precise measuring results in approx. 1 sec.
- ABS plastic housing with IP65 ingress protection rating against water and dust
- Large, easy-to-read digital LCD shows both the measured value and the temperature
- Average function measures same sample 15 times and displays the mean value
- Stainless-steel ring on sample well protects glass prism from damage
- Internal light source for improved accuracy
- Small liquid sample size of just 4 to 5 drops
- Easy calibration with distilled water
- Battery-saving automatic power off after 1 min. of inactivity

Technical specifications:

Measuring range

0 ... 28 % , 0 ... 280 ‰ salinity (salt content)

1.000 ... 1.217 SG (specific gravity)

1.3330 ... 1.3900 nD (refractive index)

0 ... +40 °C / +32 ... +104 °F temperature

Resolution

0.1% , 1 ‰ / 0.001 SG / 0.0001 nD / 0.1 °

Accuracy

±0.2 % , ±2 ‰ / ±0.002 SG / ±0.0003 nD / ±0.5 °C

General specifications

Automatic temperature compensation (ATC) range: +10 ... +40 °C / +50 ... +104 °F

Measurement speed: Approx. 1 sec.

Sample size: 4 to 5 drops of liquid

Sample well: Stainless steel ring over glass prism

Housing: ABS plastic, IP65 ingress protection rating against water and dust

Power supply: 1 x 1.5V AAA battery

Dimensions: Approx. 121 x 58 x 25 mm / 4.76 x 2.28 x 0.98"

Weight: Approx. 90 g / 0.2 lb (without battery)

Delivery contents:

1 x PCE-DRS 1 handheld digital refractometer

1 x pipette

1 x prism cover

1 x 1.5V AAA battery

1 x user manual

1 x carrying case