

Magnetometer PCE-MFM 3000



PCE-MFM 3000 Magnetometer **Portable handheld AC / DC magnetic field detector**

PCE-MFM 3000 is a handheld magnetometer that detects both static (DC) permanent magnet (rare earth) magnetic and dynamic (AC) electromagnetic fields (EMFs) and displays measurement results in gauss (G) or milli Tesla (mT). This portable magnetic field measuring device comes with an external sensor and features an RS-232 port for downloading data to a PC.

Meter can be calibrated by an ISO lab to verify accuracy, see accessories tab for information.

- ▶ Measurement range: 0 ... 30000 G / 0 ... 3000 mT
- ▶ Accuracy: $\pm 5\%$; + 20 digits (static) / + 10 digits (dynamic)
- ▶ Resolution: 0.1 G / 0.01 mT
- ▶ Detects both static (DC) permanent magnetic and dynamic (AC) electromagnetic fields (EMFs)
- ▶ Displays measurement results in gauss (G) or milli Tesla (mT)
- ▶ Comes with an external sensor
- ▶ Features an RS-232 port for downloading data to PC
- ▶ Max, min, data hold and auto shutdown power-saving functionality
- ▶ Ideal tool for checking magnetic valves, relays and air-core transformers
- ▶ Useful for assessing permanent magnets and rare earth magnets made of Neodymium Iron Boron (NdFeB), Samarium Cobalt (SmCo), Alnico and Ferrite (also known as ceramic)
- ▶ The external sensor's small, flat tip allows easy access through gaps and into tiny spaces
- ▶ Measures through casings, coverings and housings, eliminating the need to dismantle parts for inspection

Subject to change

Specifications

Static (DC) electromagnetic field (EMF) measurements

Measurement range	Sector 1: 0 ... 300 mT / 0 ... 3000 G
	Sector 2: 0 ... 3000 mT / 0 ... 30,000 G
Resolution	Sector 1: 0.01 mT / 0.1 G
	Sector 2: 0.1 mT / 1 G
Accuracy	± 5% + 10 digits

Dynamic (AC) electromagnetic field (EMF) measurements

Measurement range	Sector 1: 0 ... 150 mT / 0 ... 1500 G
	Sector 2: 0 ... 1500 mT / 0 ... 15,000 G
Resolution	Sector 1: 0.01 mT / 0.1 G
	Sector 2: 0.1 mT / 1 G
Accuracy	± 5% + 20 digits
Measurable frequencies	50 Hz / 60 Hz

General specifications

Measurement rate	1 second
Measurement direction	Uniaxial
LCD	52 x 38 mm / 2.05 x 1.50 in
Functions	Minimum value, maximum value, data hold and automatic shutdown
Operating conditions	0 ... +50°C / +32 ... +122°F, max. 85 % rh
Power supply	9V battery (included)
	Optional 9V electric power supply (see accessories)
Input current	Approx. 15 mA
Meter dimensions	198 x 68 x 30 mm / 7.80 x 2.68 x 1.18 in
Sensor dimensions	195 x 25 x 19 mm / 7.68 x 0.98 x 0.75 in
Weight	275 g / 0.61 lb

More information

Manual



More product info



Similar products



Subject to change