

Air Sampling Device PCE-MPC 30



**Air Sampling Device with data logger / HCHO measurement / battery for mobile use /
2.8 "TFT display / measurement of mass concentration / data storage on SD card**

This Air Sampling Device has many functions. With the Air Sampling Device it is possible to determine the number of particles in the size of 0.3, 2.5 and 10 μm . In addition to measuring the particles, the Air Sampling Device can also measure the PM 2.5 and PM 10 mass concentration. The mass concentration of the Air Sampling Device determines the weight of the particles on one cubic meter.

In addition to particle measurement, the Air Sampling Device can also determine the formaldehyde content in ppm. During this HCHO measurement, the temperature, the ambient humidity and the dew point are determined and displayed by the Air Sampling Device. As a further important property, the Air Sampling Device can also store data. It is therefore possible with the Air Sampling Device to evaluate all measured values after a measurement.

- ▶ Particle counter, HCHO, temperature measurement
- ▶ Measured value recording for later analyzes
- ▶ Large 2.8 "LC display, 320 x 240 pixels
- ▶ Mass concentration PM 2.5 and PM 10
- ▶ Battery for mobile use
- ▶ Dew point and wet bulb temperature

Specifications

Measurable particle sizes	PM 2.5 and PM 10
Measuring range	0 ... 2000 µg / m³
Resolution	1 µg / m³
Particle counter	
Measurable particle sizes	0.3, 2.5, 10 µm
Flow rate	2.83L / min (0.1 ft³)
Counting efficiency	50% at 0.3 µm; 100% with particle size > 0.45 µm
Coincidence error	<5% at 2,000,000 particles per ft³
Data storage	5000 data records (micro SD card)
Counting modes	cumulative, differential, concentration
HCHO	
Measuring range	0.01 ... 5.00 ppm
Accuracy	± 5%
Resolution	0.01 ppm
Air temperature and relative humidity	
Measuring range air temperature	0 ... 50 ° C, 32 ... 122 ° F
Measuring range dew point	0 ... 50 ° C, 32 ... 122 ° F
Relative humidity measuring range	0 ... 100% RH
Air temperature measurement accuracy	10 ... 40 ° C: ± 1 ° C, ± 1.8 ° F Others: ± 2 ° C, ± 3.6 ° F
Measuring accuracy dew point temperature	10 ... 40 ° C: ± 1 ° C, ± 1.8 ° F Others: ± 2 ° C, ± 3.6 ° F
Relative humidity accuracy	0 ... 20% rel. Humidity: ± 5% 20 ... 80% rel. Humidity: ± 3.5% 80 ... 100% rel. Fencing: ± 5%
More specifications	
Operating conditions	0 ... +50 ° C, 10 ... 90% rel. humidity, not condensing
Storage conditions	-10 ... +60 ° C, 10 ... 90% rel. humidity, not condensing
Display	2.8 ", 320 x 240 pixels, backlit color LCD
Power supply mains adapter	Primary: 100 ... 240 V AC, 50/60 Hz, 0.6 A. Secondary: 9 V DC, 1500 mA
Power supply battery	7.4 V, 1200 mAh, 8.88 Wh
Battery Life	approx. 4 hours in continuous operation
Battery recharge time	approx. 2 hours with AC adapter
Dimensions	240 x 75 x 57 mm
Weight	570 g

More information

More product info



Similar products



Subject to change