



PCE Americas Inc.  
711 Commerce Way  
Suite 8  
Jupiter  
FL-33458  
USA  
From outside US: +1  
Tel: (561) 320-9162  
Fax: (561) 320-9176  
info@pce-americas.com

PCE Instruments UK Ltd.  
Units 12/13  
Southpoint Business Park  
Ensign way  
Hampshire / Southampton  
United Kingdom, SO31 4RF  
From outside UK: +44  
Tel: (0) 2380 98703 0  
Fax: (0) 2380 98703 9  
info@pce-instruments.com

[www.pce-instruments.com/english](http://www.pce-instruments.com/english)  
[www.pce-instruments.com](http://www.pce-instruments.com)

## Technical Vibration Meter PCE-VDR 10

PCE-VDR 10 is a single-axis accelerometer or vibration monitor with real-time measurement and data logging capabilities. This vibration analyzer records acceleration (m/s, g, ft/s) as well as speed (mm/s, cm/s, in/s) measurements and saves the measured data to an included SD card memory. Note: To set up the SD card for the first time, the PCE-VDR 10 must be connected to AC power.

Note: To set up the SD card for the first time, the PCE-VDR 10 must be connected to AC power (AC power supply NET-LUT or NET-LUT-US sold separately - see accessories tab).

- Measures acceleration (m/s, g, ft/s) and speed (mm/s, cm/s, in/s)
- Adjustable automatic data logging
- SD card memory
- RS-232 and USB interface
- Data can be downloaded to a computer and analyzed using Microsoft Excel
- Backlit LCD screen
- Portable

### Technical Specifications

Frequency range	10 ... 1000 Hz
<b>Acceleration measuring range (at 50 m/s, 160 Hz)</b>	0.5 ... 199.9 m/s, 0.05 ... 20.39 g, 2 ... 656 ft/s
Resolution	0.1, 0.01, 1
Accuracy	± (5% of reading + 2 digits)

<b>Speed measuring range (at 50 mm/s, 160 Hz)</b>	0.5 ... 199.9 mm/s, 0.05 ... 19.99 cm/s, 0.02 ... 7.87 in/s
Resolution	0.1, 0.01, 1
Accuracy	± (5% of reading + 2 digits)
Display	LCD
Display update time	update time: 1 second
Memory	SD card (included)
Automatic data logging interval	5 ... 3600 seconds (adjustable)
Analog output	4 ... 20 mA
Power supply	6 x 1.5 V AAA batteries or 9 V DC electric power (adapter sold separately)
Interface	RS-232 and USB
Dimensions	132 x 80 x 32 mm (5.20 x 3.15 x 1.26")

### **Delivery Contents**

- 1 x Accelerometer PCE-VDR 10
- 1 x vibration sensor
- 1 x wall bracket
- 6 x 1.5 V AAA batteries
- 1 x SD memory card
- 1 x screw for 4 ... 20 mA output
- 1 x user manual