


4102

HSS DIN 9

Form.

B



ISO

3465

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
•						•	•		•	•		•					

Vc (m/min). • Optima / Optimun ○ Alternativo / Alternative



Ø Nom.	d ₁ mm	d ₂ mm	d mm	mm
*1,50	2,14	1,40	3,15	2,40
2,00	2,86	1,90	3,15	2,40
2,50	3,36	2,40	3,15	2,40
3,00	4,06	2,90	4,00	3,00
*3,50	4,56	3,40	4,50	3,00
4,00	5,26	3,90	5,00	3,80
*4,50	5,76	4,40	6,00	3,80
5,00	6,36	4,90	6,30	4,90
*5,50	7,18	5,40	6,30	4,90

L mm	l mm	mm
57	37	1
68	48	1
68	48	1
80	58	1
87	63	1
93	68	1
93	68	1
100	73	1
118	89	1

Ø Nom.	d ₁ mm	d ₂ mm	d mm	mm
6,00	8,00	5,90	8,00	6,20
*6,50	8,50	6,40	8,00	6,20
7,00	9,00	6,90	8,00	6,20
8,00	10,80	7,90	10,00	8,00
10,00	13,40	9,90	12,50	10,00
12,00	16,00	11,80	14,00	11,00
14,00	18,30	13,80	16,00	12,00
16,00	20,40	15,80	18,00	14,50
20,00	24,80	19,80	22,40	18,00

L mm	l mm	mm
135	105	1
135	105	1
135	105	1
180	145	1
215	175	1
255	210	1
270	225	1
280	230	1
310	250	1

*(Hasta fin de existencias / Jusqu'à épuisement des stocks / While supplies last)