


4109

HSS DIN 219

Form.
BTol.
H7ISO
2402

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
● 8-14	○ 6-8			● 6-8		● 12-16	● 6-12		● 14-25	● 16-25	○ 12-16	● 8-14	○ 1-3	● 2-8			

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative



➤	Ø mm	Ø int.
	32,00	16,00
	34,00	16,00
	36,00	19,00
	38,00	19,00
	42,00	19,00
	45,00	22,00
	47,00	22,00
	48,00	22,00
	52,00	27,00

L mm	l mm	📦
50	36	1
50	36	1
56	40	1
56	40	1
56	40	1
63	45	1
63	45	1
63	45	1
71	50	1

➤	Ø mm	Ø int.
	55,00	27,00
	58,00	27,00
	62,00	32,00
	65,00	32,00
	70,00	32,00
	72,00	40,00
	75,00	40,00
	80,00	40,00

L mm	l mm	📦
71	50	1
71	50	1
80	56	1
80	56	1
80	56	1
90	63	1
90	63	1
90	63	1