VG Valve thread / DIN 7756


Efficient internal thread cutting.

The short structural type makes that tap usable by hand.


The Short-Machine-Tap is also usable by machine.


A Hand-Tap-Set includes 2 taps:


- Taper Tap
- Finish Tap



Short Machine Taps
Form D for through holes and blind holes












Hand Tap Sets
for general use












Short Machine Taps
Form C for through holes and blind holes









VG	D1	D2	L1	L2	□		No.	No.	No.
DIN 2181									
VG 5 x 36	5,15	6,0	50	12	4,9	4,65	390101001	390301001	
VG 5,2 x 24	5,23	6,0	56	17	4,9	4,25	390101002	390301002	
VG 6 x 32	5,98	6,0	56	14	4,9	5,35	390101003	390301003	
VG 8 x 32	7,68	7,0	56	16	5,5	6,90	390101004	390301004	
VG 10 x 28	10,27	8,0	63	18	6,2	9,35	390101005	390301005	
VG 12 x 26	12,17	9,0	70	22	7,0	11,15	390101006	390301006	
DIN 374									
VG 5 x 36	5,15	6,0	70	12	4,9	4,65			390501001
VG 5,2 x 24	5,23	6,0	80	17	4,9	4,25			390501002
VG 6 x 32	5,98	7,0	80	14	5,5	5,35			390501003
VG 8 x 32	7,68	8,0	80	16	6,2	6,90			390501004
VG 10 x 28	10,27	8,0	90	18	6,2	9,35			390501005
VG 12 x 26	12,17	9,0	100	22	7,0	11,15			390501006