

# TABLE TYPE TEMPERATURE AND HUMIDITY TESTER CODE THT-Z158



- Table design, quiet and small
- Equipped with operating system with 7-inch touch screen controller
- Intelligent refrigeration and dehumidification system, it can save 30~45% of electricity compared with traditional machines
- Output excel data report through USB port

## SPECIFICATION

<b>Working chamber dimension(WxHxD)</b>		300x350x300mm
<b>Working chamber volume</b>		32L
<b>Temperature range</b>		-40~120°C
<b>Humidity range</b>		20~98%RH
<b>Temperature/humidity fluctuation</b>		±0.5°C, ±2.5%RH
<b>Temperature/humidity uniformity</b>		≤2°C, ±3%RH
<b>Temperature/humidity stability</b>		±0.3°C, 2.5%RH
<b>Warming up time</b>		1~3°C/min
<b>Cooling time</b>		0.7~1°C/min
<b>Operating environment</b>	<b>environment temperature</b>	5~35°C
	<b>relative humidity</b>	≤85%RH
<b>Material</b>	<b>case material</b>	Cold rolled steel plate+varnish
	<b>working chamber material</b>	SUS#304 stainless steel
	<b>thermal insulation material</b>	Polyurethane foam
<b>Freezing system</b>		Compressor
<b>Protector</b>		Compressor overload protection switch, refrigerant high pressure protection switch, ceramic fuse, water plate of water shortage protection switch, electromagnetic switch, air burn protection switch, alarm
<b>Power supply</b>		AC220,50/60HZ, 2kW
<b>Dimension(WxHxD)</b>		550x850x1050mm
<b>Weight</b>		185kg

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Test hole</b>	1pc
<b>Shelf</b>	2pcs