



BaerCoil® Thread Repair Kits

- Drill HSS
- STI Bottoming Tap HSSG
- Inserting Tool
- Tang Break Tool
- Wire Thread Inserts - type: "free running" - length: 1,5 D
- Instruction for use



G (BSP)

British Standard Pipe Thread DIN ISO 228

					 2,0 D	No.	€
G	1/8 x 28	EBW10	BZ010	9,9 mm	5	B4190	56,54
G	1/4 x 19	EBW12	BZ012	13,5 mm	5	B4191	56,54
G	3/8 x 19	EBW14		17,0 mm	5	B4192	64,79
G	1/2 x 14	EBW22			5	B4193	81,18
G	5/8 x 14	EBW24			5	B4194	174,90
G	3/4 x 14	EBW26			5	B4195	174,90
G	7/8 x 14	EBW30			5	B4196	258,50
G	1" x 11	EBW36			5	B4197	258,50
G	1.1/4 x 11	EBW42			5	B4198	*
G	1.1/2 x 11	EBW50			5	B4199	*

Please note:
 The outside diameter of 1" pipe thread is 33.25 mm (not 25.4 mm)!
 But the length of the thread insert is calculated with the value 25.4 mm:
 e.g.: Length 2 D at G 1/4 x 19: 1/4 x 25.4 mm x 2 = 12.70 mm1,5