

					TB711	TQ813	TR813	TB914 TB183 TB904 TB924	Ti914	TBE15	TBE16	TBE17	TBE18	TCH14	TQ853	TR853	TB623 TB123 TB264 TB274	TCH23		
ISO	VDI 3323	Material Description	HB	HRc	Vc (m/min.)															
P	1	Non-alloy steel	125		15-20	15-20	15-20	15-20	20-25	15-20	15-20	15-20	15-20	15-20	20-25	15-20	15-20	15-20	20-25	
	2		190	13	15-20	15-20	15-20	15-20	20-25	15-20	15-20	15-20	15-20	15-20	20-25	15-20	15-20	15-20	15-20	20-25
	3		250	25		12-18	12-18	12-18	18-24	12-18	12-18	12-18	12-18	12-18	18-24	12-18	12-18	12-18	12-18	18-24
	4		270	28		10-15	10-15	10-15	15-20	10-15	10-15	10-15	10-15	10-15	15-20	10-15	10-15	10-15	10-15	10-15
	6	Low alloy steel	180	10		10-15	10-15	10-15	15-20	10-15	10-15	10-15	10-15	10-15	15-20	10-15	10-15	10-15	10-15	15-20
M	12	Stainless steel	200	15	7-10	7-10	7-10	7-10	10-13	7-10	7-10	7-10	7-10	7-10	10-13	7-10	7-10	7-10	7-10	10-13
	13		240	23	5-8	5-8	5-8	5-8	8-11	5-8	5-8	5-8	5-8	5-8	8-11	5-8	5-8	5-8	5-8	8-11
	14		180	10	4-6	4-6	4-6	4-6	6-8	4-6	4-6	4-6	4-6	4-6	6-8	4-6	4-6	4-6	4-6	6-8
N	21	Aluminum-wrought alloy	60		10-15															
	28	Copper and Copper Alloys (Bronze / Brass)	100		15-20															
S	31	Heat Resistant Super Alloys	200	15		10-15	10-15	10-15	15-20	10-15	10-15	10-15	10-15	10-15	15-20	10-15	10-15	10-15	10-15	15-20
	36	Titanium Alloys	400Rm			10-15	10-15	10-15	15-20	10-15	10-15	10-15	10-15	10-15	15-20	10-15	10-15	10-15	10-15	15-20