

No. 6314V

Tapered clamp with adjusting support screw, complete

with DIN 787, DIN 6340, DIN 6330B. Painted tempered steel.



| Order no. | Slot | with clamping stud | H*     | sim. DIN6314 B1 x L | D x LS  | A  | B2  | E1 | E2  | Weight [g] |
|-----------|------|--------------------|--------|---------------------|---------|----|-----|----|-----|------------|
| 70268     | 10   | M10x10x80          | 8-32   | 11x80               | M10x39  | 15 | 30  | 15 | 30  | 340        |
| 70276     | 12   | M12x12x100         | 10-40  | 14x100              | M12x49  | 20 | 40  | 21 | 40  | 700        |
| 72801     | 12   | M12x12x160         | 24-92  | 14x100              | M12x94  | 20 | 40  | 21 | 40  | 830        |
| 70284     | 14   | M12x14x100         | 10-38  | 14x100              | M12x49  | 20 | 40  | 21 | 40  | 720        |
| 72827     | 14   | M12x14x160         | 23-92  | 14x100              | M12x94  | 20 | 40  | 21 | 40  | 845        |
| 70292     | 16   | M16x16x125         | 13-48  | 18x125              | M16x55  | 25 | 50  | 26 | 45  | 1400       |
| 72942     | 16   | M16x16x160         | 15-83  | 18x125              | M16x90  | 25 | 50  | 26 | 45  | 1610       |
| 70300     | 18   | M16x18x125         | 13-46  | 18x125              | M16x55  | 25 | 50  | 26 | 45  | 1400       |
| 73056     | 18   | M16x18x160         | 13-81  | 18x125              | M16x90  | 25 | 50  | 26 | 45  | 1630       |
| 70326     | 20   | M20x20x160         | 16-65  | 22x160              | M20x69  | 30 | 60  | 30 | 60  | 2600       |
| 73064     | 20   | M20x20x200         | 21-105 | 22x160              | M20x109 | 30 | 60  | 30 | 60  | 2930       |
| 70318     | 22   | M20x22x160         | 16-65  | 22x160              | M20x69  | 30 | 60  | 30 | 60  | 2770       |
| 73072     | 22   | M20x22x200         | 19-105 | 22x160              | M20x109 | 30 | 60  | 30 | 60  | 2980       |
| 373944    | 28   | M24x28x200         | 20-80  | 26x250              | M24x87  | 35 | 70  | 35 | 105 | 5486       |
| 373951    | 28   | M24x28x250         | 30-130 | 26x250              | M24x137 | 35 | 70  | 35 | 105 | 5716       |
| 381988    | 36   | M30x36x315         | 24-150 | 33x315              | M30x180 | 50 | 80  | 45 | 130 | 11995      |
| 382002    | 42   | M36x42x400         | 24-150 | 43x400              | M30x180 | 80 | 100 | 80 | 170 | 25683      |

\*depending on depth of slot to DIN 650 and position of fixture nut.  
Clamps without T-bolts are same item for sizes 12 and 14, 16 and 18, 20 and 22, each.

Recommendations



No. 6621,  
page 38

CAD

