


Flex hone brush

Design:

- rotating honing tool with abrasive globules on robust nylon brushes
- flexible working with tender grinding process
- variable nylon strings are ideal for honing of untrue or transversal bores

Use:

- for edge chamfering and for finishing of surfaces
- mountable to any machine system (among others to hand drills)
- good carrier for oil film adhesion due to cross grinding
- creates a plateau finish



N° article	481911 SiC K120	481912 SiC K180	481913 Zirconium corundum K80	B Ø mm	W Ø mm	Shank Ø mm	Trimming length mm	Total length mm
6,5	—	●	—	7	6,5	2,5	40	200
7,0	●	●	—	8	7	3,2	50	200
8,0	●	●	—	9	8	3,6	50	200
9,0	○	●	—	10	9	3,6	50	200
10,0	●	●	—	11	10	3,6	60	200
11,0	●	●	—	12	11	3,6	60	200
12,0	●	●	NEW ●	13	12	3,6	60	200
14,0	●	●	NEW ●	15,5	14	3,6	60	200
16,0	●	●	NEW ●	18	16	4,6	60	200
18,0	○	●	NEW ●	20	18	4,6	60	200
20,0	●	●	NEW ●	22	20	4,6	70	200

N° article	481911 SiC K120	481912 SiC K180	481913 Zirconium corundum K80	B Ø mm	W Ø mm	Shank Ø mm	Trimming length mm	Total length mm
22,0	●	●	—	25	22	4,6	70	200
25,0	●	●	—	28	25	5,1	70	200
29,0	●	●	—	32	29	5,1	70	200
32,0	●	●	—	35	32	5,7	70	200
35,0	○	●	—	38	35	5,7	70	200
38,0	●	●	—	41	38	5,7	70	200
41,0	○	●	—	45	41	5,7	70	200
45,0	●	●	—	48	45	5,7	70	200
51,0	○	●	—	54	51	6,5	70	200
57,0	○	●	—	60	57	7,3	70	200
64,0	—	●	—	68	64	7,5	76	200