

Benchtop Scale PCE-SCS 30



Low-cost benchtop scale up to 30 kg, Readability 2 g, Mains and battery operation, Large 20 mm LC display, Removable stainless steel platform, Zero and tare function

The benchtop scale has a 300 x 400 mm stainless steel platform that can be removed for cleaning. Flexible use of the mobile platform scale is made possible not only by the light weight and compact dimensions, but also by the independent power supply, which is possible with the 6V4Ah rechargeable battery.

If the 4 load cells of the benchtop scale with a weighing capacity of 30 kg and a resolution of only 2 g require an adjustment, this can be done quickly and easily using external weights (optional) in the calibration function of the platform scale. Thanks to the key operation, the fast response time of the platform scale and the easy-to-read 20 mm LCD display, this platform scale is ideally suited for mobile and fast weighing applications.

- ▶ Platform size 300 x 400 mm / 11.8 x 15.7"
- Shockproof plastic housing
- ▶ 20 mm LCD display
- Battery operation
- ▶ Automatic energy saving mode
- ► Tare function
- ▶ Weighing units kg and lb.
- ▶ Flat and light construction

Subject to change

Specifications

Weighing range 30 kg / 66 lb
Readability 2 g / 0.07 oz

Taring range over the full range

Settling time adjustable
Weighing units kg / lb

Display 20 mm / 0.78"LCD backlit

Platform size $300 \times 400 \text{ mm} / 11.8 \times 15.7$ " (stainless steel) Calibration by external adjustment weight (optional)

Operating temperature $-10 \,^{\circ}\text{C} \dots 40 \,^{\circ}\text{C} / 14 \,^{\circ}\text{F} \dots 104 \,^{\circ}\text{F}$

Interface RS232 Memory 18 values

Power supply 100-240V 50 / 60Hz - 12V adapter

Rechargeable battery: 6V4Ah

Battery life 130 hours

Input signal analog 10.6 mV / V - 3 mV / V

Linearity $\leq 0.01\%$ F.S.

Dimensions 480 x 560 x 150 mm / 18.9 x 22 x 5.9"

Weight 8 kg / 17.6 lb

More information

More product info



Similar products

