

Shipping Scale PCE-SW 3000N



PCE-SW 3000N is a portable battery-powered shipping scale or floor scale featuring two heavy-duty parallel weighing beams made of lacquered steel that can be positioned up to 4 m / 13 ft apart. Thus, the adjustable width accommodates multiple pallet, box and container sizes. In addition, the scale's stainless-steel-encased display can be placed up to 5 m / 16 ft away from the weighing beams, allowing for wall mounting.

- Bi-directional RS-232 interface for PC or printer connection
- Multiple TARE for whole weighing range
- Threshold, sum-up and counting functions
- ▶ 6V rechargeable battery inside display
- Ingress protection rating: IP 54
- Ideal for use in warehouse, storage facility, shipping, receiving, loading dock, logistical, supply chain, retail, inventory and stock room applications
- ▶ Software, USB to RS-232 adapter and ISO calibration certificate sold separately see accessories for details





www.pce-instruments.com

Specifications

Weighing range	3000 kg / 6613 lb (=3.3 T)
Resolution	1 kg
Accuracy	±4 kg
Tare range	Multiple tare across entire weighing range
Display	LCD with 25 mm / 1" digit height
Cable length to display ca. 5 m / 16 ft	
Interface	Bi-directional RS-232
Calibration	Multi-point calibration possible
Power supply	6V battery installed in the display (BAT-6V-4.5Ah)
Housing	Scale: painted steel / Display: stainless steel
Protection	IP 54
Environment	0 +40 °C / +32 +104 °F / 10 80% r.H.
Weight	ca. 55 kg / 121.3 lb

More information







www.pce-instruments.com