

# DIGITAL CALIPERS

- Resolution: 0.01mm/0.0005"
- Button function: on/off, zero, mm/inch, ABS, data preset
- Battery CR2032
- Made of stainless steel



DATA  
OUTPUT

1117-501

With data interface (data output cable code 7315-22, 7302-22, optional)

| Code      | Range          | Accuracy | a    | b    | c    | d     | e    | L      |
|-----------|----------------|----------|------|------|------|-------|------|--------|
| 1117-301  | 0-300mm/0-12"  | ±0.05mm  | 18mm | 56mm | 24mm | 100mm | 20mm | 420mm  |
| 1117-501  | 0-500mm/0-20"  | ±0.05mm  | 18mm | 56mm | 24mm | 100mm | 20mm | 675mm  |
| 1117-502  | 0-500mm/0-20"  | ±0.06mm  | 18mm | 56mm | 24mm | 150mm | 20mm | 675mm  |
| 1117-601  | 0-600mm/0-24"  | ±0.05mm  | 18mm | 56mm | 24mm | 100mm | 20mm | 770mm  |
| 1117-802  | 0-800mm/0-32"  | ±0.07mm  | 24mm | 67mm | 31mm | 150mm | 20mm | 1025mm |
| 1117-1002 | 0-1000mm/0-40" | ±0.08mm  | 24mm | 67mm | 31mm | 150mm | 20mm | 1220mm |

Built-in wireless (receiver code 7315-2/3/6/7/8 is required)

| Code       | Range         | Accuracy | a    | b    | c    | d     | e    | L     |
|------------|---------------|----------|------|------|------|-------|------|-------|
| 1117-301WL | 0-300mm/0-12" | ±0.05mm  | 18mm | 56mm | 24mm | 100mm | 20mm | 420mm |
| 1117-501WL | 0-500mm/0-20" | ±0.05mm  | 18mm | 56mm | 24mm | 100mm | 20mm | 675mm |
| 1117-502WL | 0-500mm/0-20" | ±0.06mm  | 18mm | 56mm | 24mm | 150mm | 20mm | 675mm |
| 1117-601WL | 0-600mm/0-24" | ±0.05mm  | 18mm | 56mm | 24mm | 100mm | 20mm | 770mm |

