


**DATA  
OUTPUT**

- The blade jaws fit into small grooves
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Made of stainless steel




**1188-150A**



**With data interface (data output cable code 7315-21, 7302-21, optional)**

Code	Range	Accuracy	L	a	b	c	d	e	g
<b>1188-150A</b>	0-150mm/0-6"	±0.03mm	235mm	21mm	16.5mm	16mm	40mm	0.85mm	17mm
<b>1188-200A</b>	0-200mm/0-8"	±0.03mm	297mm	24mm	20mm	16mm	50mm	0.85mm	17mm
<b>1188-300A</b>	0-300mm/0-12"	±0.04mm	390mm	26mm	21.5mm	16mm	60mm	1.00mm	17mm



**Built-in wireless (receiver code 7315-2/3/6/7/8 is required)**

Code	Range	Accuracy	L	a	b	c	d	e	g
<b>1188-150AWL</b>	0-150mm/0-6"	±0.03mm	235mm	21mm	16.5mm	16mm	40mm	0.85mm	17mm
<b>1188-200AWL</b>	0-200mm/0-8"	±0.03mm	297mm	24mm	20mm	16mm	50mm	0.85mm	17mm
<b>1188-300AWL</b>	0-300mm/0-12"	±0.04mm	390mm	26mm	21.5mm	16mm	60mm	1.00mm	17mm