

DIGITAL INTERNAL CALIPER GAGES

DATA
OUTPUT

- Carbide measuring tips
- Reading in digit and analog
- With transmission button and signal light
- Display can be rotated by 320°
- Button function: on/off, zero, tolerance Go and No-Go display, data preset, measuring direction change, max./min./TIR measurement, inch/metric conversion, data output, absolute/incremental measurement
- 0-6 hours automatic power off time can be set
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (code **7315-50M**, **7302-50M**, **7305-50M**)



2151-35

| Code | Range | Resolution | Accuracy | L | A | D |
|------------------|--------------------|----------------|----------|-----|----|------|
| 2151-35 | 15-35mm/0.6-1.4" | 0.01mm/0.0005" | ±0.04mm | 50 | 3 | Ø3 |
| 2151-AL35 | 15-35mm/0.6-1.4" | 0.01mm/0.0005" | ±0.04mm | 200 | 3 | Ø3 |
| 2151-55 | 35-55mm/1.4-2.2" | 0.01mm/0.0005" | ±0.04mm | 80 | 6 | Ø3 |
| 2151-AL55 | 35-55mm/1.4-2.2" | 0.01mm/0.0005" | ±0.04mm | 250 | 8 | Ø3 |
| 2151-75 | 55-75mm/2.2-3" | 0.01mm/0.0005" | ±0.04mm | 90 | 8 | Ø3 |
| 2151-AL75 | 55-75mm/2.2-3" | 0.01mm/0.0005" | ±0.04mm | 250 | 8 | Ø3 |
| 2151-95 | 75-95mm/3-3.8" | 0.01mm/0.0005" | ±0.04mm | 100 | 8 | Ø3 |
| 2151-115 | 95-115mm/3.8-4.6" | 0.01mm/0.0005" | ±0.04mm | 120 | 10 | Ø3.2 |
| 2151-135 | 115-135mm/4.6-5.4" | 0.01mm/0.0005" | ±0.04mm | 120 | 10 | Ø3.2 |

(mm)

