



16G USB flash disk (included)



0.5X camera adapter (included)




1X auxiliary objective



(included)







display cross hair (blue/green/red/yellow/ black/brown colors)



1X camera adapter (optional)



2X auxiliary objective (optional)

X-Y glass stage (optional) (X-Y travel: 74×60mm)

Built-in software without computer, operation by mouse

■ Take pictures and videos, saved to USB flash disk

SPECIFICATION

Auto focus camera

brown colors)

■ Picture review, picture compare Automatic exposure and white balance ■ Brightness, contrast ratio, gain are adjustable Display cross hair (blue/green/red/yellow/black/

SPECIFICATION		
Magnification	20X~123X	
Sensor	1/2.8" CMOS	
Pixel	2M	
Resolution	1920×1080	
Frame rate	60fps	
Output	HDMI	
Power supply	power adapter	
Dimension (L×W×H)	570×300×430mm	
Weight	6.5kg	

STANDARD DELIVERY

Main unit	1 pc
0.5X camera adapter	1 pc
1X auxiliary objective	1 pc
Calibration plate	1 pc
16G USB flash disk	1 pc
White/black plate	1 pc
Mouse	1 pc
HDMI cable	1 pc
Power adpter	2 pcs

MAGNIFICATION. FOCUS DISTANCE AND VIEW FIELD

MAGNIFICATION, FOCOS DISTANCE AND VIEW FIELD				
Auxiliary	Specification	Camera adapter		
objective		0.5X (included)	1X (optional)	
	Magnification	20~123X	40~246X	
1X (included)	Focus distance	48~84mm	48~84mm	
	View field	13×7~2.2×1mm	6.3×3.5~1.1×0.5mm	
	Measuring accuracy	±0.02mm	±0.02mm	
2X (optional)	Magnification	40~246X	80~492X	
	Focus distance	24~42mm	24~42mm	
	View field	6.5×3.5~1.1×0.5mm	3.3×1.8~0.6×0.3mm	
	Measuring accuracy	±0.02mm	±0.02mm	

AUTO FOCUS DISTANCE

Zoom objective scale	0.75X	1X	1.5X	2X	2.5X
Auto focus distance	48~84mm	50~78mm	55~73mm	62~71mm	65~70mm
Zoom objective scale	3X	3.5X	4X	4.5X	5X
Auto focus distance	66~70mm	67~70mm	68~70mm	68~70mm	68~70mm

OPTIONAL ACCESSORY

OPTIONAL ACCESSORT		
1X camera adapter	ISM-DL-CA1X	
2X auxiliary objective	ISM-DL-OB2X	
X-Y glass stage (travel: 74×60mm)	ISM-DL-STAGE	
X-Y metal stage	ISM-DL-STAGE1	
LED light	page 431~432	
Auxiliary objective	page 433	