

# PEN-TYPE DIGITAL MULTIMETER CODE 9241-ML200

- Automatic ranging
- Maximum mode
- Data hold
- Low battery display
- Auto power off
- Safety rating: CAT III 600V

## STANDARD DELIVERY

Main unit	1 pc
Probe	1 pc
Clip	2 pcs
1.5V battery	2 pcs

## SPECIFICATION

Function	Range	Resolution	Accuracy
DC Voltage	200mV/2V/20V/200V/600V	0.1mV/1mV/10mV/0.1V/1V	$\pm(0.7\%+2)$
AC Voltage	200mV/2V/20V/200V	0.1mV/1mV/10mV/0.1V	$\pm(0.8\%+3)$
	600V	1V	$\pm(1.0\%+3)$
DC Current	20mA/200mA	10 $\mu$ A/0.1mA	$\pm(1.5\%+3)$
AC Current	20mA/200mA	10 $\mu$ A/0.1mA	$\pm(2.0\%+3)$
Resistance	200 $\Omega$	0.1 $\Omega$	$\pm(1.0\%+3)$
	2k $\Omega$ /20k $\Omega$ /200k $\Omega$ /2M $\Omega$	1 $\Omega$ /10 $\Omega$ /0.1k $\Omega$ /1k $\Omega$	$\pm(1.0\%+1)$
	20M $\Omega$	10k $\Omega$	$\pm(1.0\%+5)$
Logic level test	<1.5V (green LED on) 1.5~3.5V (green & red LED off) >3.5V (red LED on)		
Diode	open circuit voltage 1.5V		
Continuity buzzer	<50 $\Omega$		
Power supply	2×1.5V AAA batteries		



clips (included)



probe (included)