DIGITAL SHORE DUROMETERS







According to ISO868, ISO7619, ASTM D 2240

- Average and peak (max.) mode
- Dwell time is adjustable
- Tolerance testing
- 500 memories
- Wireless connection to printer
- Handhold use or work with test stand (code ISH-DS-STANDA)
- Automatic power off



software CD (included)



calibration block (included)



printer (optional)

SPECIFICATION

0. 2011 10.4 110.4				
Code	ISH-DSA	ISH-DSD	ISH-DSOO	
Unit	Shore A	Shore D	Shore OO	
Test material	soft plastic, soft rubber, etc.	hard plastic, hard rubber, etc.	very soft plastic, rubber, sponge, textile, etc.	
Measuring range	0~100HA*	0~100HD *	0~100HOO	
Resolution	0.1HA	0.1HD	0.1HOO	
Accuracy	±1HA	±1HD	±1H00	
Indenter protrusion	2.5mm			
Output	wireless and USB			
Power supply	built-in rechargeable battery			
Dimension	153×50×29mm			
Weight	170g			

^{*} Use ISH-DSD when measuring result is higher than 90HA Use ISH-DSA when measuring result is lower than 20HD

STANDARD DELIVERY

Main unit	1 pc	
Calibration block	1 pc	
Software and USB cable	1 pc	
AC/DC adapter	1 pc	

OPTIONAL ACCESSORY

Printer	ISH-DS-PRINTER
Test stand	ISH-DS-STANDA